

Add SSH Key

To add SSH keys to a user profile, use the following call:

```
POST /users/:user_id/ssh_keys.xml
POST /users/:user_id/ssh_keys.json
```

XML Request example

```
curl -X POST -u user:userpass http://onapp.test/users/:user_id/ssh_keys.xml -H 'Accept: application/xml' -H 'Content-type: application/xml' -d '<ssh_key><key> ssh-rsa AAAAB3NzaClyc2EAAAABJQAAAIEAqzsLk+oPP9Qxz0Xgpqoe9DqNV7Qe3+oig/o6Ubt30Yh+Zarf8NXctqqeamC1KrlMt12d0AWd38dZ0CU6Eru/2ciwzz2IB0MLrTyjfLCNe2CW64uNjhSS1SH6gSjJUyWHSi7jUBl0v1GtJ7jswBdhgaKkjk1vXH3YFLTHPuKU+pc= user@onapp.test</key></ssh_key>'
```

JSON Request example

```
curl -X POST -u user:userpass http://onapp.test/users/:user_id/ssh_keys.json -H 'Accept: application/json' -H 'Content-type: application/json' -d '{"ssh_key":{"key":"ssh-rsa AAAAB3NzaClyc2EAAAABJQAAAIEAqzsLk+oPP9Qxz0Xgpqoe9DqNV7Qe3+oig/o6Ubt30Yh+Zarf8NXctqqeamC1KrlMt12d0AWd38dZ0CU6Eru/2ciwzz2IB0MLrTyjfLCNe2CW64uNjhSS1SH6gSjJUyWHSi7jUBl0v1GtJ7jswBdhgaKkjk1vXH3YFLTHPuKU+pc= user@onapp.test"}}'
```

Where:

*key** - a SSH key in the following format: *ssh-[type] [ascii-symbols allowed for base64 string] [user credentials]*